

QUIMIBERICA, S.A.

SAE 10W40 SEMISINTÉTICO



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Semisynthetic lubricant developed for all petrol and diesel engines of light vehicles. Adapted for engines with catalytic converter, turbocompressor and multivalve engines. It is suitable for any engine that uses unleaded fuel, LPG or bio-diesel.

PROPERTIES

- Due to its great detergent and dispersant capacity, it maintains the cleanliness of the engine, avoiding the formation of deposits and carrying particles and dust towards the oil filter.
- Protects against the wear of the most sensitive components (distribution, segment, piston, liner ...)
- It has excellent antioxidant and anti-rust properties.

TECHNICAL CHARACTERISTICS

VARIABLES	UNITS	SPECIFICATIONS
Viscosity at 100°C	cSt	13,8
Viscosity index	-	154
Flash point	°C	230
Pour point	°C	-24

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA A3/B4
API SN/CF
MB 229.1
VW 501.01/505.00

PSA B71 2294/ B71 2300
FIAT 9.55535-G2

STORAGE CONDITIONS AND EXPIRY DATE

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Date of minimum durability: 2 years.



AVAILABLE IN:

1 L
5 L
200 L
1.000 L

Edición 4 Fecha:07/05/2018

Pag. 1

This information is given for guidance and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production and do not constitute a product specification. Before using the product, it is recommended to read the information on the package. The products of Quimiberica S.A. are covered by a legal guarantee (Ley de garantías) against lack of conformity by virtue of the provisions of the General Law for the Defense of Consumers and Users (Ley General para la Defensa de los Consumidores y Usuarios- Real Decreto Legislativo 21/2007) provided that the storage conditions, specified in this technical sheet, are met. This technical sheet specifies the duration of said product warranty.