QUIMIBERICA, S.A. SAE 10W40 SINTÉTICO



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

Synthetic lubricant developed for all petrol and diesel engines. Suitable for engines with turbocompresors, multivalves and direct injection.

PROPERTIES

- Excellent protection against wear and grime thanks to its rapid lubrication from start-up and its detergent and dispersant additives.
- Its low temperature fluidity facilitates cold starts, and also offers good resistance to higher temperatures.
- High resistance to oxidation, allowing you to comply with long change intervals.

TECHNICAL CHARACTERISTICS

VARIABLES	UNITS	SPECIFICATIONS
Viscosity at 100°C	cSt	14,1
Viscosity index	-	153
Flash point	ōС	228
Pour point	ōС	-30

The characteristics mentioned represent typical values.

SPECIFICATIONS

ACEA A3/B4 API SN/CF MB 229.3 VW 502.00/505.00 RN 0700/0710

STORAGE CONDITIONS AND EXPIRY DATE

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Date of minimum durability: 2 years.



AVAILABLE IN:

1 L 5 L 200 L 1.000 L

Edición 5 Fecha:17/05/2018

Pag. 1

This information is given for guidance and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production and do not constitute a product specification. Before using the product, it is recommended to read the information on the package.

The products of Quimiberica S.A. are covered by a legal guarantee (Ley de garantias) against lack of conformity by virtue of the provisions of the General Law for the Defense of Consumers and Users (Ley General para la Defensa de los Consumidores y Usuarios-Real Decreto Legislativo 21/2007) provided that the storage conditions, specified in this technical sheet, are met. This technical sheet specifies the duration of said product warranty.