

QUIMIBERICA, S.A.

GRASA MOLIBDENO SPRAY



TECHNICAL INFORMATION

DESCRIPTION AND APPLICATION

GRASA MOLIBDENO SPRAY is a multipurpose extreme pressure lubricating grease. Grease especially recommended in periods of running-in of mechanisms. It has a limited lubrication capacity due to molybdenum disulphide. Use in the lubrication of bearings at high pressures and temperatures in the automotive, industrial and railways.

PROPERTIES

Grease formulated from highly refined paraffinic and naphthenic mineral bases, with specially selected additives and molybdenum disulphide.

TECHNICAL CHARACTERISTICS

VARIABLES	METHOD	SPECIFICATIONS
Colour	-	Dark
Consistency NLGI	-	000
Penetration, 0,1 mm, 25 °C, not worked	ASTM D 217	445/475
Worked x 60 strokes		445/475
Worked variation x 60 a x 100000		-5/+25
Dropping point, °C	ASTM D 2265	Líquida
Temperature range, °C	-	-30 to +130
Copper corrosion, 24 h, 100 °C,	ASTM 130	1/1
4 balls test, soldering load, kg.	ASTM D 2596	250/315
Oxidative stability, p.s.i. 100 h	ASTM D 942	3/5
Print diameter, 80 kg. 1 min., mm.	ASTM D 2596	0,40/0,45
Oil separation, % in weight	IP 121	3/5
Protective properties against corrosion, test SKF Emcor, distilled water	DIN 51802	0/0 – 0/0

The characteristics mentioned represent typical values.

STORAGE CONDITIONS AND EXPIRY DATE

The product does not require special storage measures.

As general storage conditions, sources of heat, radiation, electricity and contact with food should be avoided.

Store closed containers between 5 and 35°C, in a dry and well-ventilated place.

Do not expose to the sun or to temperatures over 50 °C, (spray).

Do not pierce or throw the container into the fire, not even empty, (spray).

Do not spray on a flame or incandescent body. Flammable (spray).

Date of minimum durability: 2 years.



AVAILABLE IN

Spray 520 cc

Edición 3 Fecha:31/07/2018

Pag. 1

This information is given for guidance and does not imply contractual liability. The technical data are average values and are subject to the usual fluctuations in production and do not constitute a product specification. Before using the product, it is recommended to read the information on the package. The products of Quimiberica S.A. are covered by a legal guarantee (Ley de garantías) against lack of conformity by virtue of the provisions of the General Law for the Defense of Consumers and Users (Ley General para la Defensa de los Consumidores y Usuarios - Real Decreto Legislativo 21/2007) provided that the storage conditions, specified in this technical sheet, are met. This technical sheet specifies the duration of said product warranty.